



## Assessing regional crop water demand using a satellite-based combination equation with a land surface temperature componen

**Moyano, Carmen; Garcia, Monica; Tornos, Lucia; Recuero, Laura; Palacios-Orueta, Alicia; de Juana, Luis**

*Published in:*  
Geophysical Research Abstracts

*Publication date:*  
2015

*Document Version*  
Publisher's PDF, also known as Version of record

[Link back to DTU Orbit](#)

*Citation (APA):*  
Moyano, C., Garcia, M., Tornos, L., Recuero, L., Palacios-Orueta, A., & de Juana, L. (2015). Assessing regional crop water demand using a satellite-based combination equation with a land surface temperature componen. *Geophysical Research Abstracts*, 17, [EGU2015-15503-1].

---

### General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal

If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.



## **Assessing regional crop water demand using a satellite-based combination equation with a land surface temperature component**

Carmen Moyano (1), Monica Garcia (2), Lucia Tornos (3), Laura Recuero (3), Alicia Palacios-Orueta (3), and Luis de Juana (1)

(1) Escuela Tecnica Superior de Ingenieros Agronomos. Polytechnic University of Madrid, Spain, (2) Dept. of Environmental Engineering. DTU (Denmark Technical University). Kgs. Lyngby, Denmark, (3) Escuela Tecnica Superior de Ingenieros de Montes. Polytechnic Polytechnic University of Madrid, Spain.

Quantification of daily evapotranspiration at regional levels is fundamental for improving agricultural and hydrological management, especially in water-scarce and climatic change vulnerable regions, like the Mediterranean basin. Regional estimates of daily crop evapotranspiration (ET) have been historically based on combination equations, such as Penman-Monteith or Priestley-Taylor, forced with weather-data inputs. However, the requirements for long term in-situ data, limit the application of such traditional approaches and algorithms using satellite-data without field calibrations bridge this gap by estimating long-term ET at the pixel level from local to global scales. Land surface temperature is a key variable tracking land surface moisture status. However, it has not been included in satellite ET approaches based on combination equations. In this study, a land surface temperature component was used to estimate soil surface conductance based on an apparent thermal inertia index. A process-based model was applied to estimate surface energy fluxes including daily ET based on a modified version of the Priestley-Taylor Jet Propulsion Laboratory (PT-JPL) model at 1km pixel resolution during a chrono-sequence spanning for more than a decade (2002-2013). The thermal-PT-JPL model was forced with vegetation, albedo, reflectance and temperature products from the Moderate-resolution Imaging Spectroradiometer (MODIS) from both Aqua and Terra satellites. The study region, B-XII Irrigation District of the Lower Guadalquivir, is one of the largest irrigated areas in Spain but it has scarce in-situ micrometeorological or eddy covariance data.

The final aim of this study is to evaluate the thermal version of PT-JPL model versus a lumped hydrological model (conceptual rainfall-runoff model) to assess crop evapotranspiration deficits and long-term water consumption trends in the area. The results showed that the thermal-PT-JPL model is a suitable and simple tool requiring only air temperature and incoming solar radiation apart from standard satellites-products freely available. Our results show that in comparison with the hydrological model conceptual rainfall-runoff model, requiring several meteorological and in-situ data to quantify irrigation, the satellite-based model presents a great advantage for regionalization of ET.